

# NSW1010 Series Unmanaged Ethernet Switch

## Overview

The NSW1010 series unmanaged Ethernet switch is a plug-and-play device with no configuration required. The fanless silent design completely eliminates the loud noise caused by other small switches used in the office. The small size and exquisite appearance save the space effectively. It can be widely used in industries such as network video management, hotels, campuses, small and medium-sized enterprises network, etc.

## Image

- NSW1010-5T-IN/NSW1010-5GT-IN



- NSW1010-8T-IN/NSW1010-8GT-IN



## Features

- Supports IEEE802.3 and IEEE802.3u standards.
- Supports 10/100Mbps or 10/100/1000Mbps self-adaptive Ethernet port.
- Supports auto MDI/MDIX.
- Supports IEEE802.3 flow control for full-duplex mode and backpressure for half-duplex mode.

## Specifications

Item	NSW1010-5T-IN	NSW1010-8T-IN	NSW1010-5GT-IN	NSW1010-8GT-IN
------	---------------	---------------	----------------	----------------

Service port	5 x 10/100Mbps port (RJ45)	8 x10/100Mbps port (RJ45)	5 x 10/100/1000Mbps port (RJ45)	8 x 10/100/1000Mbps port (RJ45)
Network media	10Base-T: Cat3, 4, 5 or higher UTP/STP (≤100m) 100Base-TX: Cat5 or higher UTP/STP (≤100m)		10Base-T: Cat3, 4, 5 or higher UTP/STP (≤100m) 100Base-TX: Cat5 or higher UTP/STP (≤100m) 1000Base-TX: Cat5e or higher UTP/STP (≤100m)	
Standards	IEEE802.3 (Ethernet) IEEE802.3u (fast Ethernet) IEEE802.3x (flow control)		IEEE802.3 (Ethernet) IEEE802.3u (fast Ethernet) IEEE802.3ab (Gigabit Ethernet) IEEE802.3x (flow control)	
Switching capacity	1Gbps	1.6Gbps	10Gbps	16Gbps
Packet forwarding rate	0.744Mpps	1.19Mpps	7.44Mpps	11.9Mpps
MAC	2K			
Jumbo frame	15K			
Transfer mode	Store-and-forward			
Dimensions	Product: 92*51*21.5mm Packaging: 93*82*51mm	Product: 145*60*21.5mm Packaging: 146*88*50mm	Product: 92*51*21.5mm Packaging: 93*82*51mm	Product: 145*60*21.5mm Packaging: 146*88*50mm
Carton information	Carton dimensions: 435*280*395mm Carton quantity: 100PCS Carton weight: 14.2kg	Carton dimensions: 530*475*315mm Carton quantity: 100PCS Carton weight: 17.6kg	Carton dimensions: 435*280*395mm Carton quantity: 100PCS Carton weight: 14.2kg	Carton dimensions: 530*475*315mm Carton quantity: 100PCS Carton weight: 17.6kg
Weight	Product: 0.062kg Packaging: 0.132kg	Product: 0.111kg Packaging: 0.166kg	Product: 0.062kg Packaging: 0.132kg	Product: 0.111kg Packaging: 0.166kg
Operating voltage	Adapter input voltage: AC 100V to 240V Switch input voltage: 5V, 1A			
Mount method	Desktop mount, wall mount			
Fan	Fanless	Fanless	Fanless	Fanless
Operating temperature	0°C to 40°C			
Operating humidity	10% to 90% RH, noncondensing			
Storage temperature	-20°C to 70°C			
Storage humidity	5% to 90% RH, noncondensing			
Indicator	Power: Steady on: Connected to the power Off: Disconnected to the power			
	Port: Steady on: Connected to the port Blinking: Transmitting data Off: Disconnected to the port			

## Ordering Information

### NSW1010 Series Unmanaged Ethernet Switch

Model	Remarks
NSW1010-5T-IN	5-Port 10/100Mbps Unmanaged Ethernet Switch
NSW1010-8T-IN	8-Port 10/100Mbps Unmanaged Ethernet Switch
NSW1010-5GT-IN	5-Port Gigabit Unmanaged Ethernet Switch
NSW1010-8GT-IN	8-Port Gigabit Unmanaged Ethernet Switch

#### Zhejiang Uniview Technologies Co., Ltd.

Xietong Street No. 369, Binjiang District, Hangzhou, China (310051)

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\* Product specifications and availability are subject to change without notice.