



IPC342E-VIR-Z

2MP (Motorized) VF Vandal-resistant Network IR Fixed Dome Camera



Features :

- 1/2.8" progressive scan CMOS, 2MP
- True D/N(ICR), 3D-DNR
- H.264, Triple-stream
- IP66, IK10
- DC/PoE, $\pm 25\%$ wide voltage range
- Corridor mode
- Smart IR

IPC342E-VIR-Z

2MP (Motorized) VF Vandal-resistant Network IR Fixed Dome Camera

Camera	IPC342E-VIR-Z
Sensor	1/2.8", 2 megapixel, progressive scan, low illumination CMOS
Shutter	Auto/manual, 1/6~1/8000s
Lens	3 to 10.5 mm, F1.4
Zoom/Focus	Motor drive
Angle of View (H)	102.4° (wide) to 27.4° (tele)
Min. Illumination	Color: 0.03lux(F1.4, 50IRE), black&white: 0.01lux(F1.4, 50IRE)
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR	Smart-IR , up to 30m (98 ft) IR range
Video	
Maximum Resolution	1920 × 1080
Video Compression	H.264, MJPEG
Frame Rate	1080P (1920*1080) 30 fps; 720P (1280*720) 30 fps; D1 (720*576) 25 fps
9:16 Corridor Mode	Supported
ROI(Region of Interest)	Supported
Video Streaming	Triple
Audio	
Audio Compression	G.711
Two-way Audio	Support
Storage	
Edge Storage	Micro SD, Up to 32 GB
Network	
Protocols	L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,DHCP,PPPoE,RTP,RTSP,Qos,NTP,FTP,HTTP,SNMP,SIP
Compatible Integration	ONVIF, IMOS,API
Interface	
Audio I/O	3.5 mm audio interface
Alarm I/O	2 / 1
Serial Port	1 RS485
Network	10M/100M Base-TX Ethernet
Video Output	1 BNC, impedance 75 Ω; amplitude 1 V [p-p]
General	
Power	12 V DC, or PoE (IEEE802.3 af) Power consumption: 4.5W (8.7W with IR on)
Dimensions (Ø x H)	Ø149 x 105 mm (Ø5.9" x 4.1")
Weight	0.75 kg (1.7 lb)
Working Environment	-35°C ~ +60°C (-4°F ~ 140°F), humidity ≤ 90% RH(non-condensing)
Vandal Resistant	IK10
Ingress Protection	IP66

*Product specifications and availability are subject to change without notice.

