

Quarterly Recommend Products

Zhejiang Uniview Technologies Co., Ltd. is the pioneer and leader of IP video surveillance. Heritages profound IT technologies, we founded independently in December, 2011. We are the third largest in the overall video surveillance market in China and 8th in global market. We insist on open cooperation, focusing on high quality and improving innovative ability.

Product Line:

Network camera, NVR, encoder & decoder, all-in-one VMS server, IP SAN, switch



Distributed by



www.uniview.com

Sales: overseasbusiness@uniview.com
Technical Support: globalsupport@uniview.com

2017.03 OM - 170322 XY V3.0
Disclaimer: All rights reserved, including final interpretation and content amendent.



H.265 (High Efficiency Video Coding)



H.265, known as High Efficiency Video Coding, is the new successor to Advanced Video Coding (AVC), also known as H.264. H.265 can reduce up to 50% bandwidth but keep high picture quality.

■ H.264



■ H.265



U-Code Deep Compression



U-Code is an enhanced encoding technology released by Uniview which can help to reduce up to approximately 80~95% bandwidth compared with common encoding algorithm while keeping the details clearly.

U-Code uses IRP (Intelligent Region Perception) to detect motion in each frame so that scenes containing interesting information could be preserved while the other relatively static area such as lawns, white walls could be squeezed to save storage.

Take a 4MP IPC as an example. Normally bit rate is 6Mbps, and it may roughly store 63G a day. But in U-code mode, the bit rate can be reduced up to 0.3Mbps, and it only stores 3G a day.

■ U-Code for H.265



■ U-Code for H.264




Smart Function



Intrusion detection



Crossing line detection



Face detection



People counting



Scene change detection



Defocus detection

4K Camera Series



IPC568E-G(4K)

4K Box Camera



- Optical defog
- SD/SDHC card slot
- Fiber interface

IPC6858SR-X22(4K)

IR 4K PTZ Dome Camera



- 24 VAC/24 VDC
- Up to 250m IR
- 22X optical zoom

IPC6258SR-X22P

IR 4K PTZ Dome Camera



- 24 VAC/24 VDC/PoE (PSE Required)
- Up to 200m IR
- 22X optical zoom

IPC268ER9-DZ(4K)

IR 4K Bullet Camera



- 120dB WDR
- Up to 100m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm AF motorized

IPC3238ER3-DVZ(4K)

IR 4K Fixed Dome Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm AF motorized

Starlight Camera Series



IPC262ER9-DUZ(2MP)

Starlight IR Bullet Camera



- 120dB WDR
- Up to 100m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm AF motorized

IPC262EFW-DUZ(2MP)

Starlight IR Bullet Camera



- 120dB WDR
- Up to 50m IR
- IP67
- PIR
- 2.8-12mm AF motorized

IPC262ER9-X10DU (2MP)

Starlight IR Bullet Camera



- 120dB WDR
- Up to 100m IR
- IP67
- SD/SDHC card slot
- 4.7-47mm AF motorized

IPC252ERA-X22DUG (2MP)

Starlight IR Bullet Camera



- 120dB WDR
- Up to 100m IR
- IP67
- SD/SDHC card slot
- 22X camera module

IPC3232ER3-DUV(2MP)

Starlight IR Dome Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm manual

IPC3232ER3-DUVZ (2MP)

Starlight IR Dome Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm motorized

IPC562E-DUG(2MP)

Starlight Box Camera



- 120dB WDR
- Optical defog
- ABF
- SD/SDHC card slot
- Fiber interface

IPC6252SR-X22U(G)(2MP)

Starlight PTZ Dome Camera



- 24 VAC/24 VDC
- Up to 200m IR
- IP66
- -40 °C ~ 70 °C
- 22X optical zoom
- 33X optical zoom

IPC6252SFW-X22U(2MP)

Starlight Full Spectrum PTZ
Dome Camera



- 24 VAC/24 VDC
- White Light:30m
IR:30-150m
- IP66
- -40 °C ~ 70 °C
- 22X optical zoom

IPC6252SL-X33UP(2MP)

Starlight PTZ Dome Camera



- 24 VAC/24 VDC
- IR:30m
Laser:30-500m
- IP66
- -40 °C ~ 70 °C
- 33X optical zoom

IPC6852SR-X44U(2MP)

Starlight PTZ Dome Camera



- 24 VAC/24 VDC
- Up to 250m IR
- IP66
- -45 °C ~ 70 °C
- 44X optical zoom

Network Camera



IPC2122SR3-PF40(60) -C(2MP)

Mini IR Bullet Camera



- DWDR
- Up to 30m IR
- IP67

IPC2124SR3(4MP)

Mini IR Bullet Camera



- 120dB WDR
- Up to 30m IR
- IP67

IPC2124SR3-DPF36(60) -16G(4MP)

Mini IR Bullet Camera



- 120dB WDR
- Up to 30m IR
- IP67
- 16G EMMC storage

IPC2224SR5-DPF40(60) -B(4MP)

IR Fixed Bullet Camera



- 120dB WDR
- Up to 50m IR
- IP67
- SD/SDHC card slot

IPC324ER3-DVPF(4MP)

IR Fixed Dome Camera,
3-Axis



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot

IPC322SR3-VSPF28(40) -C

IR Fixed Dome Camera,
2-Axis



- DWDR
- Up to 30m IR
- IP67
- SD/SDHC card slot

IPC3612ER3-PF(M)-C (2MP)

IR Turret Camera



- DWDR
- Up to 30m IR
- IP67
- Metal base (@M)

IPC3614SR3(4MP)

IR Turret Camera



- 120dB WDR
- Up to 30m IR
- IP67
- Metal base (@M)

IPC314SR-DVPF28(36) (4MP)

VF IR Fixed Mini Dome
Camera



- 120dB WDR
- Up to 15m IR
- IP66
- SD/SDHC card slot

IPC2322EBR5-P-C(2MP)

VF IR Bullet Camera



- DWDR
- Up to 50m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm manual

IPC2322EBR5-DPZ28-C (2MP)

VF IR Bullet Camera



- 120dB WDR
- Up to 50m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm motorized

IPC2324EBR-DPZ28 (4MP)

VF IR Bullet Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm motorized

IPC2324EBR-DP(4MP)

VF IR Bullet Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm manual

IPC3232ER-VS-C(2MP)

VF IR Fixed Dome Camera



- DWDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm manual

IPC3232ER-DV-C(2MP)

VF IR Fixed Dome Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm manual

IPC3232ER3-DVZ28-C(2MP)

VF IR Fixed Dome Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm motorized

IPC3234SR-DV(4MP)

VF IR Fixed Dome Camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm manual

IPC3234SR3-DVZ28(4MP)

VF IR Fixed Dome camera



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot
- 2.8-12mm motorized

IPC814SR-DVPF16(4MP)

Fisheye Camera



- 120dB WDR
- Up to 10m IR
- IP66
- SD/SDHC card slot
- 1.6mm

IPC742SR9(2MP)

PT IR Bullet Camera



- DWDR
- Up to 100m IR
- IP66
- Pan range 250°, tilt range -50° to 50°
- Pan speed up to 30°/s, tilt speed up to 10°/s

IPC744SR5(4MP)

PT IR Bullet Camera



- DWDR
- Up to 50m IR
- IP66
- Pan range 250°, tilt range -50° to 50°
- Pan speed up to 30°/s, tilt speed up to 10°/s

IPC6222ER-X20(P)-B(2MP)

IR PTZ Dome Camera



- P: PoE supported
- Up to 150m IR
- IP66
- -40 °C ~ 65 °C
- 20X optical zoom

IPC6222ER-X30(P)-B(2MP)

IR PTZ Dome Camera



- P: PoE supported
- Up to 150m IR
- IP66
- -40 °C ~ 65 °C
- 30X optical zoom

IPC6253SR-X33(3MP)

IR PTZ Dome Camera



- 120dB WDR
- Up to 200m IR
- IP66
- -40 °C ~ 70 °C
- 33X optical zoom

IPC2122SR3-UPF40(2MP)

Starlight Mini IR Bullet Camera



- 120dB WDR
- Up to 30m IR
- IP67

IPC322ER3-DUVPF28(40)-B(2MP)

Starlight IR Fixed Dome Camera, 3-Axis



- 120dB WDR
- Up to 30m IR
- IP67
- SD/SDHC card slot

IPC2222SR5-UPF40(60)-B(2MP)

Starlight IR Bullet Camera



- DWDR
- Up to 50m IR
- IP67
- SD/SDHC card slot

NVR



NVR301-04/08/16E



- 4/8/16-ch IP input
- 1 SATA
- 4K, H.265
- 4/1 alarm I/O
- P2P, Email, UPnP, DDNS, NTP, DHCP

**NVR301-04-P4
NVR301-08-P8
NVR301-16-P8**



- 4/8/16-ch IP input
- 1 SATA
- 4K, H.265
- 4/1 alarm I/O
- 4/8/8 PoE ports
- P2P, Email, UPnP, DDNS, NTP, DHCP

**NVR301-04L-P4
NVR301-08L-P8
NVR301-16L-P8**



- 4/8/16-ch IP input
- 1 SATA
- 4K, H.265
- Desktop housing
- 4/8/8 PoE ports
- P2P, Email, UPnP, DDNS, NTP, DHCP

**NVR302-09E-B
NVR302-16E-B**



- 9/16-ch IP input
- 2 SATA
- 4K, H.265
- 8/2 alarm I/O
- Dual network interfaces
- P2P, Email, UPnP, DDNS, NTP, DHCP

**NVR302-08E-P8
NVR302-16E-P8
NVR302-16E-P16**



- 8/16/16-ch IP input
- 2 SATA
- 4K, H.265
- 4/1 alarm I/O
- 8/8/16 PoE ports
- P2P, Email, UPnP, DDNS, NTP, DHCP

NVR304-16/32E



- 16/32-ch IP input
- 4 SATA
- 4K, H.265
- 16/4 alarm I/O
- Dual network interfaces

NVR304-16/32EP



- 16/32-ch IP input
- 4 SATA
- 4K, H.265
- 16 PoE ports
- 16/4 alarm I/O
- Dual network interfaces

NVR308-32/64E



- 32/64-ch IP input
- 8 SATA
- 4K, H.265
- 16/4 alarm I/O
- Dual network interfaces

NVR308-32/64R



- 32/64-ch IP input
- 8 SATA
- 4K, H.265
- 16/4 alarm I/O
- RAID 1, 5 & hot-swap
- Dual network interfaces

NVR516-64/128



- 64/128-ch IP input
- 16 SATA
- 4K, H.265
- 24/8 alarm I/O
- RAID 1, 5 & hot-swap
- Redundant power supply (optional)
- Extra 12 HDMI outputs extendable