

Content of Data Sheet				
Product model	CAB-6-AE/CAB-6-BE			
Product specification	HSYV-6 4×2×0.52			
Test Standard	ISO/IEC11801、TIA-568-C.2			
Conductor	Material	OFC(Oxygen free copper)		
	AWG	24		
	Nom.O.D.(mm)	0.52±0.03 mm		
	DC resistance	≤95 Ω/km		
Insulation	Material	HDPE		
	Thickness	0.2±0.02 mm		
	Diameter	0.93±0.05 mm		
	Color	Blue/White- Blue		Green/White-Green
		Orange/White-Orange	Brown/White-Brown	
Pitch	Offset pitch	≤20 mm		
	Cable pitch	≤120 mm		
Sheath	Material	PVC(complies RoHS/REACH)		
	External O.D.	5.8±0.3 mm		
	Color	Orange		
	Tensile strength	>13.5 Mpa		
	Thickness	0.6±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		
Packing	Packing	Carton		

	Once packing dimension	420mm*205mm*420mm		
	Twice packing dimension	450mm*440mm*445mm		
	Twice packing quantity	2 cases		
Packing length	305±1m			
Rip-cord	Yes	Crossing backbone	Yes	
Ambient temperature	-20°C ~ 60°C			

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com/uniarch>

©2011-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.