

UTP Category 6 Cables CCA

Content of Data Sheet				
Product model	CAB-6-CCA			
Product specification	HSYV-6 4×2×0.585			
Conductor	Material	CCA(Copper content:27%)		
	AWG	23		
	Nom.O.D.(mm)	0.585±0.05 mm		
	DC resistance	<12Ω/100m		
Insulation	Material	HDPE		
	Thickness	0.2±0.02 mm		
	Diameter	1.05±0.05 mm		
	Color			Blue/White- Blue
		Orange/White-Orange		Brown/White-Brown
Pitch	Offset pitch	≤20 mm		
	Cable pitch	≤120 mm		
Sheath	Material	PVC		
	External O.D.	6.2±0.3 mm		
	Color	White		
	Tensile strength	>13.5 Mpa		
	Thickness	0.5±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		
Packing	Packing	Carton		

	Once packing dimension	310mm*310mm*190mm		
	Twice packing dimension	400mm*330mm*330mm		
	Twice packing quantity	2		
Packing length	100±1m			
Rip-cord	Yes	Crossing backbone	Yes	
Ambient temperature	-20°C ~ 60°C			

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.