

Specifications

Device	Description
Video compression	H.265/H.264
Camera support	1 to 16
Image composition	Supports composition of 2/3/4/6 images
Image operations	Supports image storage, retrieval, view, export, and upload
Image OSD	Supports text overlays including license plate, lane, time, location, etc.
HDD	4 × 3.5" SATA slot
Interface	Description
Network	Dual NICs, supports network isolation and interconnection 2 × 1000M self-adaptive Ethernet electrical port, 4 × 100M Ethernet electrical port; 1 × 1000M Ethernet optical port, 4 × 100M Ethernet optical port
USB	2 × USB3.0 (compatible with USB2.0)
Serial port	3 × RS-232, 4 × RS-485
Alarm input	8 × alarm input interface (Phoenix terminal)
Alarm output	4 × alarm output interface (Phoenix terminal)
Power output	DC12V, 500mA
Power input	DC12V, 10A
Hardware	Description
Power consumption	≤ 20W (without HDD, with heating off) ≤ 105W (full-load 4T HDDs, with heating on)
Operating temperature	-30°C to 70°C
Operating humidity	5% to 95% RH, non-condensing
Weight	Without HDD < 7kg Full-load HDDs < 9.5kg
Dimensions	350mm(W) × 320mm(D) × 70mm(H)

Ordering Information

Model	Quantity	Remarks
ISC2500-SCT-G-OS	1	ISC2500-SCT-G-OS ITS terminal

Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

* Product specifications and availability are subject to change without notice.