


UTP Category 5E Cables

Content of Data Sheet				
Product model	CAB-LC5E-BU			
Product specification	Quality verified by latest standard AS/CA S008:2020			
Test Standard	ISO/IEC11801 、TIA-568-C.2、IEC61156-6			
Conductor	Material	Solid-Bare Copper		
	AWG	25		
	Nom.O.D.(mm)	0.45±0.005 mm		
	DC resistance	≤115 Ω/km		
Insulation	Material	HDPE		
	Thickness	0.17±0.01 mm		
	Diameter	0.81±0.05 mm		
	Color	Blue/White- Blue	Green/White-Green	
		Orange /White-Orange	Brown/White-Brown	
Pitch	Offset pitch	≤25 mm		
	Cable pitch	≤140 mm		
Sheath	Material	PVC(complies RoHS/REACH)		
	External O.D.	4.7±0.3 mm		
	Color	Blue		
	Tensile strength	>13.5 Mpa		
	Thickness	0.55±0.05 mm		
Surface Printing	Letter height	3.0±0.3 mm		
	Color	Black		
	Print error & Space	1±0.005 m		
	Case number	Yes		



Packing	Packing	Carton + Plastic shaft
	Once packing dimension	297mm*257mm*310mm
	Twice packing dimension	545mm*320mm*335mm
	Twice packing quantity	2 cases
Packing length	305±1 m	
Rip-cord	Yes	
Ambient temperature	-20°C ~ 60°C	

Zhejiang Uniview Technologies Co.,Ltd.

No.369,Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, Zhejiang Province, China(310051)

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2023 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.