

VS-R5328S-C2X@AI General-Purpose Mid-Range AI Server



Overview

This mid-range 2-socket 2U rack server is designed based on 3rd-generation Intel® Xeon® Scalable processors. It uses high-performance Intel® C621 series chipsets which perfectly support various latest NVIDIA® GPU-accelerated services to deliver robust performance in a limited space and meanwhile provide scalability and high availability.

Features

High performance

- 3rd-generation Intel® Xeon® Scalable processors.
- Newly upgraded high-speed PCIe 4.0 bus, fully utilizing GPU compute capacity.
- Large-capacity storage plus 8 graphics cards for acceleration, providing comprehensive processing capabilities for AI online reasoning.

High reliability

- 12 3.5/2.5-inch HDDs, compatible with NVMe SSD, allowing personalized storage configuration.
- Optional 1+1 power redundancy design supports PMBus, module-loss alarm and more to enhance server operation security.

Low power consumption

- Green energy-saving design, energy-efficient intelligent speed regulation, and multiple working modes such as optimized overclock, power balance, and green energy-saving for different operating characteristics and environments of GPU.
- Health monitoring and reporting functions for key components facilitate data center operation and maintenance.

Specifications

Parameters	Description
Processor	Intel®4314 Xeon*2
RAM	Standard 32G*4, total 32 slots
Management	1*1000Mbps network interface dedicated for IPMI remote management
Network interface	10GE*2, support PCIe network interface expansion
USB interface	4*USB 3.0 (2 rear, 2 front)
Serial interface	1 (rear)
Video interface	2*VGA interfaces (1 rear, 1 front)
HDD bays	4
Standard HDD	4T SATA HDD*1, 1.92T SATA R SSD*1
Front HDD expansion	4*2.5/3.5-inch SAS/SATA/SSD HDDs, expandable to 12*2.5/3.5-inch SAS/SATA/SSD HDDs
PCI-E card slots	8*PCI-E 4.0 slots
Built-in RAID controller	1 (sold separately)
Graphics card	Supports 8* low profile graphics cards (such as T4 card) Sold separately
Power supply	1+1 redundancy
Dimensions	87.8mm(H)x446mm(W)x794mm(D)
Power input	AC: 220V DC: 240V
Weight	38KG (fully loaded)
Environment temperature	Operating: 5°C to 35°C Non-operating: -40°C to 60°C
Relative humidity	Operating: 35% to 80% Non-operating: 20% to 93%

Order Info

Product Code	Qty	Remarks
VS-R5328S-C2X@AI	1	UNV,VS-R5328S-C2X@AI Universal Mid-end AI Server, Domestic Version
MEM-32G-DDR4-B	Opt.	Module-UNV-MEM-32G-DDR4-B, 32GB DDR4 Memory Bank, Domestic version
RAID-8i-2G-B	Opt.	Module-UNV-RAID-8i-2G-B-2GB cache 8 Ports RAID Card, Domestic version
VS-SSD-1920E-A-B	Opt.	Module-UNV-VS-SSD-1920E-A-B-1.92T SATA Interface SSD, Domestic version
NIC-10G-2P-B	Opt.	Module-UNV-NIC-10G-2P-B-10-gigabit Duplex NIC, Domestic version
NIC-1G-2P-B	Opt.	Module-UNV-NIC-1G-2P-B-Gigabit Duplex NIC, Domestic version

Zhejiang Uniview Technologies Co., Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.