

SSD-1024G-P3-M2 SSD

Overview

U3000 series SSD is an M.2 2280 SSD that features small size, low heat generation, and low power consumption. It has four PCIe Gen3 interfaces, provides up to 3100MB/s sequential read speed and a minimum of 1300MB/s sequential write speed, which is faster and more efficient than traditional HDD and SATA SSD products.



Interface	M.2
Dimensions	80mmx22mmx2.3mm (LxWxH)
Weight	Max 8g
Max sequential read	3000MB/s
Max sequential write	2600MB/s
Max random read (4KB)	222K
Max random write (4KB)	164K
Operating temperature	0°C to 70°C
Storage temperature	-40°C to 85°C
Operating humidity	≤90% RH (non-condensing)
MTBF	≥1500000 hours

Ordering Information

Item	Description
Model	SSD-1024G-P3-M2
Description	1024G PCIe3 NVMe U3000 SSD
Capacity	1024GB
Storage media	3D TLC

Item	Remarks
SSD-1024G-P3-M2	Storage media-3D TLC-1024G-PCIe3 NVMe-U3000 SSD-UNV

Zhejiang Uniview Technologies Co., Ltd.

South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P. R. China 310051

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2022 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

***Product specifications and availability are subject to change without notice.**